



234 Venture Street, San Marcos Ca 92078
Phone: 760-510-1298 Fax: 760-874-2973

PREDATOR SOFT TOP ROOF RACK SYSTEM

Product Information:

Thank you for your recent purchase of our Soft Top Roof Rack System for your H1 Hummer. You own one of the most advanced designed Performance upgrades for your H1 Hummer.

IMPORTANT: To ensure proper function and safety, you **MUST** have Roof Rack System installed by a trained professional. Failure to do so will void warranty and possibly cause injury. Predator Motorsports will not be liable for misuse, neglect or improper installation. Additionally, Predator makes no claims to compatibility of factory or aftermarket warranties.

Warranty Information:

Your Predator Roof Rack System is backed by a Lifetime Warranty on all structural parts including all spacers and brackets under normal use by the original purchaser. Misuse such as a roll-over, rally racing and other similar use will not be covered under warranty. Powder Coating, Plating and other finishes are covered for 3 years.

Item List:

- 1- 6' Soft Top Roof Rack
- 1- Soft Top Slant Back
- 1- Light Bar
- 4- Mounting Brackets for Roof Rack
- 8- 3/8"x2.5" Bolts Nuts and Washers (Roof Rack Mount Hardware)
- 8- 3/8"x1.25" Bolts Nuts and Washers (Roof Rack Mount Hardware)
- 20-5/16"x1.25 Bolts Nuts Washers (Slant Back)
- 2- 3/8"x2.5" Bolts Nuts (Light Bar)

Installation Procedure:

1. Install Front Light Bar with the supplied 3/8" Bolts by removing factory outer two hinge bolts located on the outer lower corners of the windshield and the two 1/4" Phillips head screws located at the center marker light bracket. Carefully slip lightbar into place and slide bolts into place with the washer located on the outside. Note: we recommend using a layer of tape over the mounting surface to prevent scratching. Install the factory Phillips bolts into the upper mounts and tighten. Tighten lower mounts.
2. Install Slant Back Tire Carrier onto the bed of the Hummer. Slide forward and back to desired location. Mark hole location on corner of bed. Remove Slant back and drill the 20 3/8" holes. Clean and prep the holes with paint. Cut rubber pads into sections and mount onto the bottom surface of the mounting holes on Slant Back. Re-install slant back onto bed and tighten bolts into place.
3. Loosely install the four mounting brackets onto the light bar and slant back with the long side facing inward. Use supplied 3/8"x1.25" bolts nuts and washers. (note: do not tighten)
4. Carefully set Roof Rack onto mounts. Use supplied 3/8"x2.5" bolts and loosely tighten.
5. Align roof rack and tighten lower bolts on both the front and back of Roof Rack. Tighten upper bolts through the roof rack.
6. Double check that all bolts are secure and tight.

Questions about the installation or operation of your Slant Back Roof Rack? Call toll-free 877-733-2867, 760-510-1298 or e-mail support@predatormotorsports.com

