



1250 Distribution Way, Vista Ca 92081
Phone: 760-510-1298 Fax: 760-874-2973

PREDATOR SLANT BACK TIRE CARRIER

Product Information:

Thank you for your recent purchase of our Slant Back Tire Carrier for your H1 Hummer. You own one of the most advanced designed upgrades for your H1 Hummer.

IMPORTANT: To ensure proper function and safety, you **MUST** have the Slant Back Tire Carrier installed by a trained professional. Failure to do so will void warranty and possibly cause injury. Predator Motorsports will not be liable for misuse, neglect or improper installation. Additionally, Predator makes no claims to compatibility of factory or aftermarket warranties.

Warranty Information:

Your Predator Slant Back Tire Carrier is backed by a Lifetime Warranty on all structural parts including all spacers and brackets under normal use by the original purchaser. Misuse such as a roll-over, rally racing and other similar use will not be covered under warranty. Powder Coating, Plating and other finishes are covered for 3 years.

Item List:

- 1- Slant Back Rack
- 1- Tire Mount (threaded Shaft Mount, Spinner and Bushing)
- 4- 1/2" x1.5" Bolts Nuts Washers (Tire Mount)
- 20-5/16"x1.25 Bolts Nuts Washers (Slant Back)
- Rubber Pads

Installation Procedure:

1. Install Slant Back Tire Carrier onto the bed of the Hummer.
2. Slide forward and back to desired location.
3. Mark hole locations on corner edge of fender/bed.
4. Remove Slant back and drill 3/8" holes on marked location on fender.
5. Clean and prep the holes with paint.
6. Cut rubber pads into sections and mount onto the bottom surface of the mounting holes on Slant Back.
7. Re-install slant back onto bed and tighten bolts into place.
8. Double check that all bolts are secure and tight.

Questions about the installation or operation of your Slant Back Roof Rack? Call toll-free 877-733-2867, 760-510-1298 or e-mail support@predatormotorsports.com



