



1250 Distribution Way, Vista CA 92081 Phone: 760-734-1749 Fax: 760-874-2973

	PRODUCT NUMBER H2-PER-778 / H2-PER-779
--	--

H2 Predator Air Intake System

Congratulations on the purchase of your new accessory by Predator Motorsports. As with all products, proper installation is the key to obtaining all of the benefits your accessory is capable of delivering. Please take a few minutes to read through the instructions to identify the components and learn where and how they are used. It is a good idea to start by comparing the parts in your kit with the parts list below. Be sure to take all applicable safety precautions during the installation of this product.



Parts List	Quantity	Parts List Continued	Quantity
Intake Tube	1	Couplers (large and small)	2
Reusable Air Filter Element	1	Hose Clamp	4
Shroud Seal	1	“L” Bracket	3
Metal Shroud	1	Male-Male Isolator Bushing	2
Hardware Box	1	Male-Female Isolator Bushing	1

INSTRUCTIONS

1. Open hood.
2. Remove stock air filter box cover by loosening the two screws.
3. Remove air filter element
4. Remove stock air intake tube.
5. Remove air filter box by removing the bolts located under air filter element.
6. Separate MAF sensor from intake box.



Installation Procedure

1. Install shroud seal on shroud. (See Fig.1)
2. Install maf sensor on shroud using supplied small allen head bolts and nylocks. (See Fig.2)
3. Install all isolator bushings on inside of shroud with the male-female in the center hole. Use supplied hardware. (See Fig. 1,3,4)
4. Install “L” brackets onto isolator bushings with only the center bracket facing out towards engine. (See Fig. 1,3,4)
5. Set shroud assy. into place and secure with stock hardware. (See Fig. 1,3,4)
6. Install air intake tube using the supplied couplers with the larger one located on the MAF sensor. Tighten all clamps and hardware.
7. Install Hi-Flow air filter element and tighten.



Fig.1



Fig.2



Fig.3



Fig.4



Fig.5



Fig.6

Copyright 2005 Predator Motorsports
Predator Motorsports Inc. - Vista, CA USA
www.predatormotorsports.com