

		<b>PRODUCT NUMBER</b> <b>H2-INT-734</b>
<b>BILLET AIR VENT RING INSTRUCTION MANUAL</b>		
<p><i><b>Congratulations</b></i> on the purchase of your new accessory by Predator Motorsports®. As with all products, proper installation is the key to obtaining all of the benefits your accessory is capable of delivering. Please take a few minutes to read through the instructions to identify the components and learn where and how they are used. It is a good idea to start by comparing the parts in your kit with the parts list below. Be sure to take all applicable safety precautions during the installation of this product.</p>		
<b>Parts List</b>	<b>Quantity</b>	<b>Tools Required</b>
Large Air Vent Ring	3	<ul style="list-style-type: none"> <li>• Windex/cleaner</li> </ul>
Large-Thin Air Vent Ring	1	
Small Air Vent Ring	2	

**INSTRUCTIONS**

***Preparation***

1. Prepare a clean, flat, non-abrasive (cloth covered) surface to place the rings on.
2. Place adhesive strips on table and verify the proper quantity and size are present.
3. Gently peel protective backing from one side of adhesive strip and align with inside of trim ring. Gently press adhesive onto trim ring and carefully trim any excess from ends or edges if necessary.
4. Repeat step 3 for each additional ring.



**Installation Procedure**

1. Clean the surrounding area of each vent with glass cleaner or similar cleaning solution approved for use on the painted dash surface.
2. Place the trim ring up to dash panel and verify the proper location of EACH ring.
3. Once the proper location is determined, gently peel protective backing from adhesive and carefully align with dash panel making certain that the indentations are at the 3,6,9 and 12 o'clock positions.
4. Once aligned to dash panel, press firmly into place.
5. Repeat steps 2 through 4 for each additional ring.

