



PRODUCT NUMBER
H2-INT-735

BILLET DOOR SILL INSTRUCTION MANUAL

Congratulations on the purchase of your new accessory by Predator Motorsports Inc. As with all products, proper installation is the key to obtaining all of the benefits your accessory is capable of delivering. Please take a few minutes to read through the instructions to identify the components and learn where and how they are used. It is a good idea to start by comparing the parts in your kit with the parts list below. Be sure to take all applicable safety precautions during the installation of this product.



<u>Parts List</u>	<u>Quantity</u>	<u>Tools Required</u>
Large (Front) Door Sill	2	<ul style="list-style-type: none"> • Cleaner
Small (Rear) Door Sill	2	<ul style="list-style-type: none"> • Soft Towel

INSTRUCTIONS

Removal Procedure

1. Identify and remove the 4 factory doorsills (2 front; 2 rear), by gently and carefully prying up the plastic sill. They are double-sided taped onto the vehicle, so you will need to apply a generous amount of effort to pull the sill free from the body
2. It is important to remove all of the factory tape and residue from the sill. This can be done with 3M Adhesive Remover or rubbing alcohol.
3. You need to prep the sill area where you will be installing the Predator sill. This can be done with 3M Adhesive Remover, rubbing alcohol, or similar surface prep solutions.

Installation Procedure

1. Peel the adhesive back from the Predator Sill and install. Be sure to align it before you stick as once it makes contact; it is very hard to remove. **NOTE:** *Our rear sill is shorter than the factory.*

