



1250 Distribution Way, Vista, CA 92081  
Phone: 760-510-1298 Fax: 760-874-2973  
H3 Fuel Door

### Warranty Information:

Your Hummer H3 Fuel Door is backed by a Lifetime Warranty on all structural parts including all spacers and brackets under normal use. Misuse and neglect is not covered under warranty. All hardware and finish such as chrome or anodizing, is backed by our 4 year 50,000 mile warranty. To ensure a lifetime of trouble free use, you must wash and wax the finish on the door once a month in dry climates and once a week in wet climates. We also recommend silicone spray lube to be shot into the lock and hinge points every month.

### Tools Needed for Installation:

10mm Wrench  
10mm Socket  
8mm Wrench  
8mm Socket  
Flat Head Screwdriver

### Item List:

1- H3 Billet Fuel Door  
5- 5mmx25mm set screws  
5- Washers  
5- Nylock Nuts  
2- Barrel Keys

### Installation:

1. Remove Fuel Door Bezel. The fuel door bezel snaps into place and needs to be jerked abruptly out to dislodge. See image 1.
  2. Remove fender shroud by removing snap clips and bolts. Drop the rear part of the fender shield down. Remove the rear bumper corner located just below the fuel door. See Image 2 and 3.
  3. Using a pair of diagonal cutters or dremel tool, remove/cut 5 of the 7 snaps from the fuel door bezel. Be careful not to crack the bezel. Cut out the top two and bottom three clips. See image 4.
  4. Unscrew the top two nuts holding the fuel filler neck in place and dismount the filler neck from the threaded mounts.
  5. Slide fuel door bezel behind the rear quarter panel and over filler neck. Reinstall filler neck onto mounts and tighten nuts.
- Note: when installing door bezel you may have to rotate shroud and spin it over the filler neck. See image 5 and 6.
6. Install the 5 set screws into the back side of the fuel door and tighten in place. Align fuel bezel with quarter panel holes and slide fuel door into place. Install washers and nuts on back side of the door and tighten. See image 7.
  7. Reinstall Bumper Corner and Fender Shroud.



Image 1



Image 2



Image 3



Image 4



Image 5



Image 6



Image 7

